

Unmanaged Megabytes Switch

GNT-E9008EL

- 8 ports 100Mbps
- 6KV Lightning & 8KV ESD Protection
- Compact Design, Competitive Solution


Ports Description




1

1 100Mbps Ports

Dimension (mm)



Installation Diagram



Specifications

| | |
|---------------------------|---|
| Model | GNT-E9008EL |
| Ports | (1~8):10/100Mbps ports (RJ45) |
| Transmission Rate | 10/100Mbps: Full Duplex / Half Duplex |
| Transmission Distance | 100m |
| Performance Specification | Bandwidth:1.6Gbps |
| | Network Latency (10 to 100Mbps): $\leq 16\mu s$ (use the 64byte package size) |
| | MAC address table: 2K |
| | Packet Forwarding Rate: 1.2Mpps |
| Networking Standard | IEEE 802.3i 10BASE-T |
| | IEEE 802.3u 100BASE-TX |
| | IEEE 802.3x Flow Control |
| Power Support | Power Input: AC 90~264V 3W |
| Physical Specifications | Size(L*W*H): 138mm*70mm*25mm, Weight: 0.2KG |
| Working Environment | Operating Temperature: -30°C~60°C |
| | Storage Temperature: -40°C~70°C |
| | Operating Humidity: 10%~90% Non-condensing |
| | Storage Humidity: 5%~90% Non-condensing |
| Certification | CE |
| | FCC |
| | RoHS 2.0 |
| Warranty | Whole Device: 1 year |
| Package Content | User Manual |