

Network Switch

GNT-G1008EL

- 8 ports 1000Mbps
- 6KV Lightning & 8KV ESD Protection
- Compact Design, Competitive Solution


Ports Description




1

1 1000Mbps Ports

Dimension (mm)



Installation Diagram



Specifications

Model	GNT-G1008EL
Ports	(1~8):10/100/1000Mbps ports (RJ45)
Transmission Rate	1000Mbps: Full Duplex Only 10/100Mbps: Full Duplex / Half Duplex
Transmission Distance	100m
Performance Specification	Bandwidth:16Gbps
	Network Latency (10 to 1000Mbps): $\leq 16\mu s$ (use the 64byte package size)
	MAC address table: 8K
	Packet Forwarding Rate:11.9Mpps
Networking Standard	IEEE 802.3i 10BASE-T
	IEEE 802.3u 100BASE-TX
	IEEE 802.3ab 1000BASE-T
	IEEE 802.3x Flow Control
Power Support	Power Input: AC 90~264V 3W
Physical Specifications	Size(L*W*H): 138mm*70mm*25mm, Weight: 0.2KG
Working Environment	Operating Temperature: -30°C~60°C
	Storage Temperature: -40°C~70°C
	Operating Humidity: 10%~90% Non-condensing
	Storage Humidity: 5%~90% Non-condensing
Certification	CE
	FCC
	RoHS 2.0
Warranty	Whole Device: 1 year
Package Content	User Manual